



900 Series

Hot-Water Pressure Washers with 1725 RPM Motors

North America's #1 Manufacturer of High-Quality Cleaning Equipment

Electric / Belt Drive



Model 9825S
with Natural Gas Fired combustion chamber

Upright, oil fired burner delivers high efficiency and maintains constant temperature using diesel fuel, kerosene or home-heating oil

Stainless-steel coil skin provides extra durability to withstand the elements, resist corrosion and endure rough treatment

Thermal rupture disk protects the machine and user from heat expansion

Adjustable upstream detergent injection provides high-pressure sudsing for better cleaning

Water-resistant cabinet, electrical box and motor

Hose reel (optional) makes hose mobility and storage easy and convenient. Keeps work areas neat and safe while protecting hose from damage

50-ft. length of high-pressure hose (shown on reel) and **hanger** for ease in cleaning around a large area

Easy to understand **operating instructions** and warning labels

5 HP Baldor, 1725 RPM electric motor is drip proof and comes with thermal overload protection

Built-in wand holder provides convenient storage

Control panel includes adjustable temperature control, plus heavy-duty heater and pump motor switches

Convenient **hose reel bracket** (standard) accepts swivel or stationary reels



Hotsy-designed triplex belt-drive pump carries a 7-year limited warranty

Every Hotsy comes with 35 years of experience and rugged durability built-in

Rust-proof, removable, non-contaminating polyethylene fuel tank includes fuel gauge in cap. Tank is oversized to provide for long-running operating time (standard on oil-fired models)

Wheel kit and handle make for easy portability (standard on oil-fired models)

Heavy-duty fuel filter protects burner fuel pump

Semi-pneumatic wheels eliminate the risk of flats

Model 9805S: Oil Fired, 3.9 GPM @ 2000 PSI

Insulated Hotsy Trigger Gun, rated to 3750 PSI. **36" insulated wand** with ergonomic, adjustable side handle



Float tank helps maintain constant water pressure and flow and helps prevent sediment from entering the machine's components...great for use in well-water environments and low-water situations

FEATURES

- 3.9 GPM @ 2000 PSI
- Oil Fired, LP or Natural Gas Fired
- 230V, 1PH; 208V, 230V or 460V, 3PH
- ETL-Certified to UL-1776 safety standards

900 SERIES Hot-Water ELECTRIC Models with 1725 RPM Motors

■ Oil Fired, LP or Natural Gas Fired ■ 3.9 GPM @ 2000 PSI ■ Hotsy Triplex Pump with 7-yr warranty ■ ETL-Certified for safety

Designed for tough, industrial cleaning.

SPECIFICATIONS

BELT DRIVE

MODEL	GPM	PSI	HP	MOTOR RPM	VOLT/PH	AMP	FUEL	PUMP	PUMP RPM	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)
980SS	3.9	2000	5	1725	230/1	29	Oil	Hotsy Triplex	970	Belt	Std	50'	520
981SS	3.9	2000	5	1725	230/1	25	LP	Hotsy Triplex	970	Belt	NA	50'	615
982SS	3.9	2000	5	1725	230/1	25	NG	Hotsy Triplex	970	Belt	NA	50'	545
990SS	3.9	2000	5	1725	230/3	19	Oil	Hotsy Triplex	970	Belt	Std	50'	550
990SS-208	3.9	2000	5	1725	208/3	20	Oil	Hotsy Triplex	970	Belt	Std	50'	560
991SS	3.9	2000	5	1725	230/3	16	LP	Hotsy Triplex	970	Belt	N/A	50'	520
991SS-208	3.9	2000	5	1725	208/3	18	LP	Hotsy Triplex	970	Belt	N/A	50'	530
992SS	3.9	2000	5	1725	230/3	16	NG	Hotsy Triplex	970	Belt	N/A	50'	520
992SS-208	3.9	2000	5	1725	208/3	18	NG	Hotsy Triplex	970	Belt	N/A	50'	595
993SS	3.9	2000	5	1725	460/3	10	Oil	Hotsy Triplex	970	Belt	Std	50'	580
994SS	3.9	2000	5	1725	460/3	8	LP	Hotsy Triplex	970	Belt	N/A	50'	525
995SS	3.9	2000	5	1725	460/3	8	NG	Hotsy Triplex	970	Belt	N/A	50'	525

Dimensions: 45"l x 18"w x 48"h



Clean better with Hotsy detergents

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all 40 Hotsy detergent formulations contain Hotsy's

exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.

Spend some time with a Hotsy Expert

Hotsy has more than 130 local Sales & Service Distributors in North America, all factory-trained to properly evaluate your high-pressure cleaning needs.

Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.



Distributed by:



Tel: (800) 525-1976 Fax: (888) 880-9631
 www.Hotsy.com email: info@Hotsy.com
 P/N 97-0470 Effective 2/05 Specifications & product descriptions subject to change without notice. ©2005 Hotsy

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ± 5% of listed specifications.

OPTIONS for 900 SERIES with 1725 RPM Motors

- **Primary & Additional Remote Stations** provide easy operation in wash bays or multiple stations
- **Shutdown Timer** allows automatic machine shutdown
- **Auto Start/Stop** provides preset & adjustable on/off machine operation
- **8" Natural Gas or LP Gas Fired Draft Diverters** prevent backdrafts; keeps cold air out & prevents water from running down vent pipes
- **8" Oil-Fired Draft Dampener**; barometric; prevent back drafts; keeps cold air out

Hotsy Accessories customize your application for top performance



360° Pivot and non-pivot hose reels keep hose neatly stored and shop areas safe



High-pressure turbo nozzles for faster cleaning




Remote control box allows pressure washer to be located in one room; controls and wands in other rooms

Telescoping wands extend to 24' to reach high places without scaffolding



Heavy-duty, high-pressure hoses in lengths up to 150-ft.



Rotary surface cleaner attaches to your pressure washer; reduces overspray and zebra striping



Foamers increase dwell time on vertical surfaces, such as tractor trailers, walls and crates